

# 4735

## UHF DMR Desktop Radio



### General Properties

- Analog and Digital Mode
- Appropriate to DMR Standard
- User Notifications and Alerts
- LCD Screen
- Alphanumeric Keypad
- Graphical User Interface
- Call Log
- Caller ID
- 3 Level RF Power Level
- Channel Search
- Sending Time Limit
- Menu Authorization
- Computer Aided Repair
- Appropriate to MIL-STD-810C/D/E/F/G Standards
- Appropriate to ETSI 300-086 (Analog), ETSI 300-113 (Digital:DMR) Standarts

### Digital Mode Properties

- Group Call
- Individual Call
- Emergency Call
- SMS ( Radio to Radio)
- Data Communication (with data software pack)
- Status Message
- Encryption (Optional)
- Phone Book
- Call Alert

### Standards

IEC 61149	MIL-STD-810C/D/E/F/G
ETSI EN 300 086-2	TTTE Directive
ETSI EN 300 113-2	TIA-102.CAAB-D
ETSI EN 301 489-1,5	TIA-603-D
ETSI EN 60950	

## 4735

## UHF DMR Desktop Radio



## General Technical Specifications

Modulation	Analog FM, 4FSK (DMR)
Channel Range	12,5 / 25 kHz (Analog) 12,5 kHz (DMR)
Data Speed (Digital)	1,8 kb/s
Voice Encoder	AMBE++
Encryption Algorithms	AES
Channel Number	256
Power Supply	13,6 Vdc $\pm$ 20%
Power Supply Input Voltage	220 Vac $\pm$ 20%
Screen	64 x 128 pixel LCD
Keypad	20 key (backlit)
Dimensions (HxWxD)	67 x 297 x 227 mm
Power Supply Dimensions (HxWxD)	67 x 297 x 212 mm
Weight	3,50 kg
Operation Temperature	-30°C / +60°C
Storage Temperature	-40°C / +85°C
Humidity	95% @ 50°C

## Receiver Technical Specifications

Frequency Range	380-470 MHz
Audio Output Power	7W / 8 $\Omega$
Max. Sensitivity	<-110 dBm
Intermodulation Rejection	$\geq$ 70dB
Spurious Response Rejection	$\geq$ 70 dB
Adjacent Channel Selectivity (12,5 kHz channel)	$\geq$ 60dB
Audio Distortion	$\leq$ 5%

## Transmitter Technical Specifications

RF Output Power	10-40 W
Frequency Accuracy (-30°C / +60°C; 25°C ref)	$\pm$ 2 ppm
Modulation Limitation(12,5 kHz channel)	$\pm$ 2,5 kHz
Transmitted Spurious Broadcasting	-36 dBm @ < 1 GHz

Communication and Information Technologies

T: (312) 592 10 00 F: (312) 354 13 02

www.aselsan.com.tr

hbtmarketing@aselsan.com.tr